HULK LED 200W IP65 5000K

HIGH-BAY AND LOW-BAY

LED GO!







LED | □ | IP65 | IK08 | C €

TECHNICAL PARAMETERS

374135 Index: IP65 Ingress protection: 200 Rated power [W]: Luminous flux [lm]*: 25150 Colour temperature [K]: 5000 Colur rendering index: >80 Electrical protection class: Ш Energy efficiency class: Α+ Material of the body: aluminium Diffuser type: MAT


CHARACTERISTICS

HIGH-BAY type LED fitting, in which high-power LED modules with an opal diffuser were used. Made of powder coated aluminum, in RAL9006 colour. As a standard, it is equipped with power supply with a DIMM 1-10V dimmer. Distribution angle: 120°. Colour temperature 5000K, CRI>80, lifespan of LED 50 000h (L70B50) ta= 25 °C.

APPLICATION

The fitting is designed for suspended installation, both for outside and internal use. Perfect for manufacturing plants and halls, as well as large-format warehouses.

LIGHT CURVES





^{*}Tolerance +/- 10%

HULK LED 200W IP65 5000K

HIGH-BAY AND LOW-BAY



TECHNICAL PARAMETERS TABLE

Material of the body:

aluminium

and the second s		5 L 5 L L L	
Light source:	LED	Colour of the body:	grey
Rated power [W]:	200	Dimensions [mm]:	355/355/353
Supply voltage [V]:	220 - 240	Impact resistance:	IK08
Frequency [Hz]:	50 - 60	Ingress protection:	IP65
Luminous flux [lm]:	25150	Mounting version:	suspended
Luminous efficacy [lm per W]:	125	Working temperature [°C]:	od -30 do +35
Energy efficiency class:	A+	Net weight of the luminaire [kg]:	5
Electrical protection class:	II	CE certificate:	15/2017
Colour temperature [K]:	5000	Index:	374135
Colur rendering index:	>80	EAN:	5905963374135
LED lifespan [h]:	50000	Category type:	high-bay and low-bay
Radiation angle [°]:	105	Mark D:	tak / yes
Diffuser material:	PC	Lamp power factor:	0,97
Diffuser type:	MAT		

^{*}Tolerance+/- 10%









