

PRODUCT-DETAILS

NC08/100M

STND WEIGHT NYL COND NC08 100M BLK



General Information

Extended Product Type	NC08/100M
Product ID	7TCA298000R0188
EAN	5020963023002
Catalog Description	STND WEIGHT NYL COND NC08 100M BLK
Long Description	Standard Weight, General Purpose Conduit, NC Size 08/NW Size 7.5, Outside Diameter 10.0mm, Inside Diameter 6.5mm, Static Bend Radius 15mm, High Flexibility and Fatigue Life, IP40 Rating, Polyamide 6, Reel Length 100 Meters, Black

Ordering

EAN	5020963023002
Customs Tariff Number	3926909990

Dimensions

Product Net Weight	4.42 lb 2.005 kg
--------------------	---------------------

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Extensively Used in Harnesses on HGV and off Road Vehicles Applications Where Superior Protection Against Impact and Mechanical Shock is Preferred. The Conduit is Used for Both Chassis and Engine Applications and Can Be Used in a Wide Range of Temperatures
Brand / Label	Harnessflex
Color	Black
Flexibility	Very High
Inside Diameter	6.5 mm
Material	Polyamide/Nylon 6
Nominal Size	NC08/NW7.5
Number of Batteries	0
Outside Diameter	10.0 mm
Product Name	"flexible conduit, nylon"
Product Type	Standard Weight Conduit
Radius	Static: 15 mm
Standards	ADR Approved, RoHS, Conforms with End of Life Vehicle Directive (ELV) EU200/53/EC
UPC	786210146867

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	NC08/100M
Declaration of Conformity - CE	9AKK107492A9616
Instructions and Manuals	NC08/100M

Classifications

ETIM 6	EC001175 - Corrugated plastic hose
ETIM 7	EC001175 - Corrugated plastic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5540 >> Flexible Non-Metallic Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

