

PRODUCT-DETAILS

CTPA16-S/100M

L/WEIGHT NYL SLIT COND NC16 100M BL



General Information

Extended Product Type	CTPA16-S/100M
Product ID	7TCA298000R0052
EAN	5020963021527
Catalog Description	L/WEIGHT NYL SLIT COND NC16 100M BL
Long Description	Lightweight Weight, Extra Flexible Slit Conduit, NC Size 16/NW Size 13, Outside Diameter 16.0mm, Inside Diameter 11.8mm, Static Bend Radius 35mm, High Fatigue Life and Abrasion, Impact Resistance, IP40 Rating, Polyamide 6, Reel Length 100 Meters, Black

Ordering

EAN	5020963021527
Customs Tariff Number	3926909990

Dimensions

Product Net Weight	6.39 lb 2.898 kg
--------------------	---------------------

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	37 in 940 mm

Package Level 1 Height	17 in 432 mm
Package Level 1 Depth / Length	17 in 432 mm
Package Level 2 Units	6 piece
Package Level 2 Width	37 in 940 mm
Package Level 2 Height	17 in 432 mm
Package Level 2 Depth / Length	17 in 432 mm

Additional Information

Application	General Purpose, Lightweight Loom Applications
Brand / Label	Harnessflex
Color	Black
Flexibility	High
Inside Diameter	11.8 mm
Material	Polyamide/Nylon 6
Nominal Size	NC16/NW13
Number of Batteries	0
Outside Diameter	16.0 mm
Product Name	nylon conduit
Product Type	Slit Lightweight Conduit
Radius	Static: 35 mm
Special Functions	Self Extinguishing, Low Smoke Toxicity & Halogen Free
Standards	RoHS, Conforms with End of Life Vehicle Directive (ELV)EU200/53/EC
UPC	786210147949

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	CTPA16-S/100M
Declaration of Conformity - CE	9AKK107492A9616
Instructions and Manuals	CTPA16-S/100M

Classifications

ETIM 6	EC001175 - Corrugated plastic hose
ETIM 7	EC001175 - Corrugated plastic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5540 >> Flexible Non-Metallic Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

