

FPCB system spiral reinforced pvc

FPCG, FPCGN & FPCBU system r**FL**US

spiral reinforced pvc with special properties

IP65

Conduit

FPCB

Colour: Black

FPCG

colour grey.

63

FPC63B

UL recognised.



Construction: Smooth bore, helically formed PVC, flexible conduit with spiral UPVC reinforcement and flexible PVC jacket. Also available in UL recognised version (See ordering notes)

Typical Applications: Routing of cables within machines.

Typical Applications: As FPCB.

FPCGN

Construction: Smooth bore, helically formed PVC, flexible conduit with spiral UPVC reinforcement and flexible PVC jacket. Colour: Green

Typical Applications: As FPCB but where oil resistance is required. UL recognised.

Fittings

МРС

straight nylon compression fitting external thread

2 part compression fitting with internal spigot and all round external teeth to grip conduit. Available in Black or Grey (RAL 7001).



FPCBU Construction: As FPCB except

colour blue. Typical Applications: As FPCB but where high temperature is required. UL recognised.

| nominal size (mm) | FPC | Black part number | Grey (RAL 7001) | Green (RAL 6001) | Blue (RAL 5012) | min inside bend radius (mm) | reel length (m) | outside dia (mm) | inside dia (mm) |
|-------------------|---------|-------------------|-----------------|------------------|-----------------|--------------------------------|-----------------|------------------|-----------------|
| 12 | FPC | 12B | FPC12G* | FPC12GN* | FPC12BU* | 30 | 14.5 | 10.0 | 25 |
| 16 | FPC | 16B | FPC16G* | FPC16GN* | FPC16BU* | 30 | 16.5 | 12.0 | 25 |
| 16 | | | | | | | | | |
| 20 | FPC | 20B | FPC20G* | FPC20GN* | FPC20BU* | 30 | 21.0 | 16.0 | 35 |
| 25 | FPC25B | | FPC25G* | FPC25GN* | FPC25BU* | 30 | 27.5 | 22.0 | 45 |
| 30 | FPC30B* | | FPC30G* | | | 30 | 30.5 | 25.0 | 55 |
| 32 | FPC | 32B | FPC32G* | FPC32GN* | FPC32BU* | 10, 30 | 33.5 | 28.0 | 60 |
| 40 | FPC4 | 40B | FPC40G* | FPC40GN* | FPC40BU* | 10, 30 | 41.0 | 35.0 | 80 |
| 50 | FPC | 50B | FPC50G* | FPC50GN* | FPC50BU* | 10, 30 | 46.4 | 40.0 | 105 |

FPC63GN* FPC63BU*

10, 30

57.0

50.0

120

| metric thread part number | PG thread part number | NPT part number |
|------------------------------|--------------------------|--------------------|
| MPC-12-M16 | MPC-12-PG9 | |
| MPC-16-M16 | MPC-16-PG11 | |
| MPC-16-M20 | MPC-16-PG13 | MPC-16-050 |
| MPC-20-M20 | MPC-20-PG16 | MPC-20-050 |
| MPC-25-M25 | MPC-25-PG21 | MPC-25-075 |
| MPC-30-M32* | MPC-30-PG29* | |
| MPC-32-M32 | MPC-32-PG29 | MPC-32-100 |
| MPC-40-M40 | MPC-40-PG36 | MPC-40-125 |
| MPC-50-M50 | MPC-50-PG42 | MPC-50-150 |
| MPC-63-M63 | MPC-63-PG48 | MPC-63-200 |



FPC63G*

Ordering Notes

- Add reel length eg: FPC20B-30M for 30M
- * Indicates parts made to order on request and may be subject to MOQ and lead time
- For UL recognised black conduit order FPCURB*
- · Available on request:
- additional sizes
- alternative threads
- other colours

