


**NEW**


FPP	FCL	FCLAMP	EC	REC
<p><b>Construction:</b> Standard weight polypropylene, flexible conduit.</p> <p><b>Colour:</b> Black, Grey (RAL 7031) or White (see page 71)</p> <p><b>Typical Applications:</b> Buildings, particularly where buried in concrete or plaster.</p> <ul style="list-style-type: none"> <li>• Acid resistant</li> <li>• Temperature range -20°C to +90°C</li> <li>• Self extinguishing</li> <li>• Slit version also available FPP-S</li> </ul> <p><b>Other options available:</b></p>	<p><b>nylon corrugated conduit clip with integral lid</b></p> <p>Nylon PA66 conduit clip with integral lid for increased security. Incorporates internal ribs to prevent corrugated conduit from pulling through, 20 Kg with FPAS21.</p>	<p><b>non-metallic, heavy duty conduit clamp</b></p> <p>Nylon PA66, conduit fixing clamp for corrugated conduit. Suitable for use with fine or coarse pitch conduits. Can be used with a range of accessories including cover plates and weld plates (available separately - see page 76).</p>	<p><b>end cap</b></p> <p>Nylon PA66 end cap to snap over end of conduit and provide a smooth entry bush to prevent snagging and sharp edges, and provide a neat finish when no connectors are used.</p>	<p><b>rubber end cap</b></p> <p>Thermoplastic elastomer cap used to seal end of conduit. Can be cut to size depending on size of cable. Can be additionally secured using cable tie (not supplied).</p>

**FPP-NFR**



LSOH conduit for data cabling applications.

**FPPH**



Heavy weight conduit for buried underground applications.



FPP	part number	reel length (m)	outside dia (mm)	inside dia (mm)	min inside bend radius (mm)				pitch	nominal size (mm)	european (NW) sizes
						Conduit Clip	FCLAMP	End Cap			
FPP10	50	10.0	6.3	15	FCL10			REC10	10	0-7	F 10 7
FPP13	50	13.0	9.8	25	FCL13			REC13	13	0-7	F 13 10
FPP16	50	15.8	11.8	35	FCL16	FCLAMP- 3-16	EC16B	REC16	16	0-11	F 16 12
					FCL18						F 18 14
FPP20	50	20.0	14.8	40	FCL20						C 20
FPP21	50	21.2	16.7	40	FCL21	FCLAMP- 3-21	EC21B	REC21	21	0-15	F 21 17
					FCL21	FCLAMP- 3-21	EC21B	REC21	21	0-15	C 21
FPP25	50	25.0	19.1	50	FCL25						C 25
FPP28	50	28.5	22.8	55	FCL28	FCLAMP- 4-28	EC28B	REC28	28	0-21	F 28 23
					FCL28	FCLAMP- 4-28	EC28B	REC28	28	0-21	C 28 23
FPP34	25, 50	34.5	28.1	65	FCL34	FCLAMP- 5-34	EC34B	REC34	34	0-25	C 34 29
					FCL34	FCLAMP- 5-34	EC34B	REC34	34	0-25	F 34 29
FPP42	25	42.5	35.5	80	FCL42	FCLAMP- 6-42	EC42B	REC42	42	0-34	C 42 36
FPP54	25	54.5	47.2	100	FCL54	FCLAMP- 7-54	EC54B	REC54	54	0-46	C 54 48
FPP67	10	67.2	56.3	150		FCLAMP- 7-67		REC67	67	0-52	C 67 56

For larger diameter conduit see page 74  
 NOTE: FPP - NFR and FPPH.  
 Contact us for more details

F = fine pitch C = coarse pitch

## Ordering Notes

- Specify colour (B = Black, G = Grey) and reel length eg: FPP16B-50M for a Black 50m reel
- Some lengths are MTO in Grey
- Available on request:
  - longer lengths and bulk packaging
  - cut lengths and assemblies
  - additional sizes
  - other colours
- conduit with pre-installed draw wire
- FPADS in Polypropylene (PP)

