

Flexarm | CENALED SPOT Flexarm

ON / OFF and dimming button

Sheathed and steplessly repositionable gooseneck

Die-cast aluminium

Safety glass, crack-proof, 4 mm

High performance LED chips

Screw-on base, prepared for further fastening options, e.g., a magnetic base (screws included)

CENALED SPOT Flexarm DC

version 24 V DC

- 24V DC
- IP67
- 3m

version 100–305 V AC

- 100 V / 305 V AC
- IP65
- 3m

Icons: ≥80, 5000K, +50/-10, 36 months, Germany flag, 60.000h (L80/B10)

CENALED SPOT Flexarm	Product no.	Length of arm (A)	Base (B)	Optics	E _{max} *	Lamp luminous flux	Output	Connection
CENALED SPOT Flexarm DC, screw-on base	121012-01	500 mm	59 mm	30°	9212 lx	1120 lm	~8,5 W	24V DC
CENALED SPOT Flexarm AC, screw-on base	121012-11	500 mm	88 mm	30°	9212 lx	1120 lm	~9 W	100-305V AC

Power supply, dimmboxes and connection materials, see Accessories.

* maximum lighting intensities, measurement area 100 cm x 100 cm at 50 cm distance

Accessories	Product no.
Holding magnet for CENALED screw-on base	220500-01
Table clamp for CENALED screw-on base	220500-02
Wall bracket for CENALED screw-on base	220500-03



The CENALED SPOT is part of the CENALED modular system. The basic module of every light is the screw-on base for a 24V DC or 100-305 VAC connection. The modular structure is supplemented with an articulated arm, flexible arm or a directly mounted swivel head. The lamp head has an on/off switch and brightness control (dimming).

The screw-on base allows several optional fastening options, for example using a magnetic clamp or a table clamp.

