


CB12245A Battery Charger

One product for the field: 12 and 24 Vdc



Input: Single-phase 115 ÷ 277 Vac

Output Jumper Selectable: 12 Vdc 6A; 24 Vdc 5 A

Power Supply Function: setting by Jumper

Suited for the following battery types: Open Lead Acid, Sealed Lead Acid, lead Gel, Ni-Cd, Li-Ion (option)

Battery Care for, automatic diagnostic of battery status, short circuit element,

Charging curve IUoU, constant voltage and current

Switching technology Semi-resonant

Four charging levels: Boost, Absorption, Float, Recovery.

Protected against short circuit, inverted polarity, over Load.

Signal output (contact free) for fault battery state

Protection degree IP20 - DIN rail

Technical features

The CB series is a "Switching technology" and "Battery Care philosophy", since years parts of the core know-how at ADEL system, led to the development of this advanced multi-stage battery charging method, completely automatic and suited to meet the most advanced requirements of battery manufacturers. The Battery Care concept is based on algorithms that implement rapid and automatic charging, battery charge optimization during time, flat batteries recovery and real time diagnostic during installation and operation. The Real Time Auto-diagnostic system, monitoring battery faults such as, elements in short circuit, accidental reverse polarity connection, disconnection of the battery, they can easily be detected and removed by help of Blink Code of Diagnosis Led; during the installation and after sell. Each device is suited for all battery types, by means of jumpers it is possible setting predefined curves for Open Lead Acid, Sealed Lead Acid, Gel, Ni-Cd. A rugged casing with bracket for DIN rail mounting provide IP20 protection degree.

Input Data

Nominal Input Voltage	100 – 240 – 277 Vac
Input Voltage range	90 – 305 Vac
Inrush Current (Vn and In Load) I ² t	≤ 16 A ≤ 5 msec.
Frequency	47 – 63 Hz ±6%
Input Current (115 – 270 Vac)	2.4 – 1.2 A
Internal Fuse	4 A
External Fuse (recommended)	10 A (MCB curve B)

Battery Output 24 Vdc (depend on jumper selection)

Boost charge (Typ. at In)	28.8 Vdc
Recovery Charge	2 – 18 Vdc
Charging. Max I _{batt} < 40°C(In) Input V. 230Vac	5 A ± 5%
Charging. Max I _{batt} < 40°C(In) Input V. 120Vac	4 A ± 5%
Charging. Max I _{batt} > 40°C(In)	3.5 A ± 5%

Battery Output 12 Vdc (depend on jumper selection)

Boost charge (Typ. at In)	14.4 Vdc
Recovery Charge	2 – 9 Vdc
Charging. Max I _{batt} < 40°C (In)	6 A ± 5%
Charging. Max I _{batt} > 40°C (In)	6 A ± 5%

Generic Output Data

Max. time Boost Charge (typ. At In)	15 h
Min. time Boost Charge (typ. At In)	4 min.
Jumper Configuration battery type (V cell) Ni-Cd (optional); when in Float Charging mode	2,23; 2,25; 2,3; 1,41–1,5 (20 cell.)
Power Supply function	By Jumper Enabling
Select Output Voltage 12 or 24 Vdc	By Jumper Enabling
Select Boost or float charge	By Jumper Enabling
Efficiency (50% of In)	90%
Dissipation power load max (W)	20.5
Charging current limiting I _{adj}	20 ÷ 100 % / I _n
Quiescent Current (Input main Voltage ON)	≤ 5mA
Quiescent Current (Input main Voltage OFF)	0mA V _{batt} < 26.3
Charging Curve automatic: IUoU	4 stage
Detection of element in short circuit	Yes
Short-circuit protection)	Yes
Over Load protection	Yes
Over Voltage Output protection	Yes

Connection and Monitoring

Signal Output (free switch contact)

Main or Backup Input Power	Yes
Low Battery	Yes
Fault Battery	Yes

Type of Signal Output Contact (free switch contact)

Max. current can be switched (EN60947.4.1):	
Max. DC1: 30 Vdc 1 A; AC1: 60 Vac 1A	Resistive load
Min.1mA at 5 Vdc	Min. load

General Data

Insulation voltage (In / Out)	3000 Vac
Insulation voltage (In / PE)	1605 Vac
Insulation voltage (Out / PE)	500 Vac
Protection Class (EN/IEC 60529)	IP20
Protection class	I, with PE connected
Reliability: MTBF IEC 61709	> 300.000 h
Pollution Degree Environment	2
Connection Terminal Blocks screw Type	2,5mm(24–14AWG)
Dimensions (w-h-d)	45x110x100 mm
Weight	0.30 Kg approx.

Climatic Data

Ambient temperature (operation)	-25 ÷ +70°C
De Rating T ^a > 50°C	- 2.5%(In) / °C
Ambient temperature Storage	-40 ÷ +85°C
Humidity at 25 °C no condensation	95% to 25°C
Cooling	Auto Convection

Norms and Certifications

Conforming to: UL1236, Safety EN IEC 62368-1: 2014/AC:2015; EMC Directive 2014/35/UE and Low voltage Directive 2014/35/UE; Emission: IEC 61000-6-3, Immunity: IEC 61000-6-2, CE

Charging

Type of charging it is Voltages and Current stabilized IUoU DIN41773 (Charging cycle). The state of charging battery and Auto-diagnosis of the systems are identified by a blinking code on a Diagnosis LED and Battery Fault LED:

Chargin g Type	State	Diagnosis LED	Battery Fault LED
Auto diagnosis	Float	1 Blink/2sec	OFF
	Absorption	1 Blink/sec	OFF
	Boost – Bulk	2 Blink/sec	OFF
	Recovery	5 Blink/sec	OFF
s	Reverse polarity	1Blink	ON
	Battery No connect	2Blink	ON
	Element in Short C.	3Blink	ON

